

VIZA.EX26538 - Fittings, Grooved and Plain End

Fittings, Grooved and Plain End

[See General Information for Fittings, Grooved and Plain End](#)

SHANDONG LUYUAN FIRE TECHNOLOGY CO LTD

EX26538

STATION OF FANG AN SUB-DISTRICT OFFICE

FANGZI DISTRICT

WEIFANG, SHANDONG 261210 CHINA

The following fittings are intended for use with Shandong Luyuan Fire Technology Co Ltd's (EX26539) Listed rubber gasketed fittings.

Grooved End

Model	Type	Size In.	Rated Pressure (psig)
XGQT01	90 degree elbow	1, 1-1/4, 1-1/2, 2, 2-1/2, 3 OD (76.1 mm), 3, 4-1/4 OD (108.1 mm), 4, 5-1/4 OD (133 mm), 5-1/2 OD (139.7 mm), 6-1/4 OD (159 mm), 6-1/2 OD (165.1 mm), 6, 8, 10	300
XGQT02	45 degree elbow	1, 1-1/4, 1-1/2, 2, 2-1/2, 3 OD (76.1 mm), 3, 4-1/4 OD (108.1 mm), 4, 5-1/4 OD (133 mm), 5-1/2 OD (139.7 mm), 6-1/4 OD (159 mm), 6-1/2 OD (165.1 mm), 6, 8, 10	300
XGQT03	Equal tee	1, 1-1/4, 1-1/2, 2, 2-1/2, 3 OD (76.1 mm), 3, 4-1/4 OD (108.1 mm), 4, 5-1/4 OD (133 mm), 5-1/2 OD (139.7 mm), 6-1/4 OD (159 mm), 6-1/2 OD (165.1 mm), 6, 8, 10	300
XGQT13	Grooved reducer tee	2 x 1, 1-1/4, 1-1/2; 3 OD (76.1 mm) x 1, 1-1/4, 1-1/2; 3 x 1, 1-1/4, 1-1/2, 2; 4 x 1, 1-1/4, 1-1/2, 2, 2-1/2, 3 OD (76.1 mm), 3; 5-1/2 OD (139.7 mm) x 1, 1-1/4, 1-1/2, 2, 2-1/2, 3 OD (76.1 mm), 3, 4; 6-1/4 OD (159 mm) x 1, 1-1/4, 1-1/2, 2, 2-1/2, 3 OD (76.1 mm), 3, 4; 6-1/2 OD (165.1 mm) x 1, 1-1/4, 1-1/2, 2, 2-1/2, 3 OD (76.1 mm), 3, 4; 6 x 1, 1-1/4, 1-1/2, 2, 2-1/2, 3 OD (76.1 mm), 3, 4; 8 x 4, 6-1/2 OD (165.1 mm)	300
XGQT13S	Threaded reducer tee	2 x 1, 1-1/4, 1-1/2; 3 OD (76.1 mm) x 1, 1-1/4, 1-1/2; 3 x 1, 1-1/4, 1-1/2, 2; 4 x 1, 1-1/4, 1-1/2, 2, 3 OD (76.1 mm), 3; 5-1/2 OD (139.7 mm) x 1, 1-1/4, 1-1/2, 2, 3 OD (76.1 mm), 3; 6-1/4 OD (159 mm) x 1, 1-1/4, 1-1/2, 2, 3 OD (76.1 mm), 3; 6-1/2 OD (165.1 mm) x 1, 1-1/4, 1-1/2, 2, 3 OD (76.1 mm), 3, 4; 6 x 1, 1-1/4, 1-1/2, 2, 3 OD (76.1 mm), 3, 4	300
XGQT14	Cross	1, 1-1/4, 1-1/2, 2, 2-1/2, 3 OD (76.1 mm), 3, 4-1/4 OD (108.1 mm), 4, 5-1/4 OD (133 mm), 5-1/2 OD (139.7 mm), 6-1/4 OD (159 mm), 6-1/2 OD (165.1 mm), 6, 8	300

XGQT07	Reducer grooved	2 x 1, 1-1/4, 1-1/2; 3 OD (76.1 mm) x 1-1/4, 1-1/2; 3 x 1-1/4, 1-1/2, 2, 3 OD (76.1 mm); 4 x 1-1/4, 1-1/2, 2, 3 OD (76.1 mm), 3; 5-1/2 OD (139.7 mm) x 1-1/4, 1-1/2, 2, 3 OD (76.1 mm), 3, 4; 6-1/4 OD (159 mm) x 1-1/4, 1-1/2, 2, 3 OD (76.1 mm), 3, 4; 6-1/2 OD (165.1 mm) x 2, 3 OD (76.1 mm), 3, 4, 5-1/2 OD (139.7 mm); 6 x 2, 3 OD (76.1 mm), 3, 4; 8 x 2, 3 OD (76.1 mm), 3, 4, 6-1/2 OD (165.1 mm)	300
XGQT07S	Reducer threaded	2 x 1, 1-1/4, 1-1/2; 3 OD (76.1 mm) x 1, 1-1/4, 1-1/2, 2; 3 x 1, 1-1/4, 1-1/2, 2; 4 x 1, 1-1/4, 1-1/2, 2, 2-1/2, 3 OD (76.1 mm), 3; 5-1/2 OD (139.7 mm) x 1, 1-1/4, 1-1/2, 2, 2-1/2, 3 OD (76.1 mm), 3; 6-1/4 OD (159.1 mm) x 1, 1-1/4, 1-1/2, 2, 2-1/2, 3 OD (76.1 mm), 3; 6-1/2 OD (165.1 mm) x 1, 1-1/4, 1-1/2, 2, 2-1/2, 3 OD (76.1 mm), 3, 4; 6 x 1, 1-1/4, 1-1/2, 2, 2-1/2, 3 OD (76.1 mm), 3, 4; 8 x 1, 1-1/4, 1-1/2, 2, 2-1/2, 3 OD (76.1 mm), 3, 4	300
XGQT08	Grooved flange adapter	2, 2-1/2, 3 OD (76.1 mm), 3, 4-1/4 OD (108.1 mm), 4, 5-1/4 OD (133 mm), 5-1/2 OD (139.7 mm), 6-1/4 OD (159 mm), 6-1/2 OD (165.1 mm), 6, 8, 10	300
XGQT6S	Threaded flange adapter	2, 3 OD (76.1 mm), 3, 4	300
XGQT09	Cap	1, 1-1/4, 1-1/2, 2, 2-1/2, 3 OD (76.1 mm), 3, 4-1/4 OD (108.1 mm), 4, 5-1/4 OD (133 mm), 5-1/2 OD (139.7 mm), 6-1/4 OD (159 mm), 6-1/2 OD (165.1 mm), 6, 8	300

Trademark and/or Tradename: "LUYUAN"

Last Updated on 2018-11-28

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"